EKAMANT

SAFETY DATA SHEET FOR COATED ABRASIVES

I.PRODUCT RKJFN
2. INGREDIENTS
2.1 ABRASIVES
X Syntethic corundum (aluminium oxide)
Silicon carbide
Zircon corundum (zirkon oxide + aluminium oxide)
Others
2.2 COATING SUPPORT
2.2 COATING SUPPORT
Paper
X Cotton cloth
Polyester cloth
Combination paper/cloth
Uulcanised fibre
Others
2.3 BOND 2.3.1 BONDING AGENT
Glue (Natural material derived from plant or animal)
X Polymerized thermosetting resin
Others

Registered Office

Ekamant Production AB

P.O. Box 114

S-285 23 MARKARYD

Reg. No.

556551-9468

V.A.T. No.

SE556551946801

Phone No.

Int +46 - 433-79 700

Fax No.

Int +46 - 433-79 797



X Calcium carbonate
X Kaoline
Kryolite
Others
2.4 OTHER INFORMATION
Extra coating with stearat.
3. PHYSICAL PARTICULARITIES
X Partially soluble in water
Insoluble in water (waterproof)
4. STORAGE AND FIRE PROTECTION
X Store at 20 °C (± 5 °C) and at 50-65% relative humidity
X Not included within the "dangerous products"
X The coating and the bonding are combustible
Particular safety measure are not necessary. In case of fire, foam carbon oxide or extinction dust can be used for extinction
5. PROTECTION AT WORK
• Adequate dust extraction should be provided and appropriate protective clothing worn.
• Directive for the protection of workers and the recommendations so machine manufacturers as well as the directives for the prevention of accidents should be followed.
6. WASTE DISPOSAL
• Federal, State and Local laws should be followed.
7. OTHER CONSIDERATIONS
X None
See over