

EKAMANT

SAFETY DATA SHEET FOR COATED ABRASIVES

1. PRODUCT

UMAYD

2. INGREDIENTS

2.1 ABRASIVES

- Synthetic corundum (aluminium oxide)
- Silicon carbide
- Zircon corundum (zircon oxide + aluminium oxide)
- Others

2.2 COATING SUPPORT

- Paper
- Cotton cloth
- Polyester cloth
- Combination paper/cloth
- Vulcanised fibre
- Others

2.3 BOND

2.3.1 BONDING AGENT

- Glue (Natural material derived from plant or animal)
- Polymerized thermosetting resin
- Others

Registered Office

Ekamant Production AB

P.O. Box 114

S-285 23 MARKARYD

Reg. No.

556551-9468

V.A.T. No.

SE556551946801

Phone No.

Int +46 - 433-79 700

Fax No.

Int +46 - 433-79 797



- Calcium carbonate
- Kaoline
- Kryolite
- Others

2.4 OTHER INFORMATION

3. PHYSICAL PARTICULARITIES

- Partially soluble in water
- Insoluble in water (waterproof)

4. STORAGE AND FIRE PROTECTION

- Store at 20 °C (\pm 5 °C) and at 50-65% relative humidity
- Not included within the "dangerous products"
- The coating and the bonding are combustible

Particular safety measure are not necessary. In case of fire, foam carbon oxide or extinction dust can be used for extinction

5. PROTECTION AT WORK

- Adequate dust extraction should be provided and appropriate protective clothing worn.
- Directive for the protection of workers and the recommendations so machine manufacturers as well as the directives for the prevention of accidents should be followed.

6. WASTE DISPOSAL

- Federal, State and Local laws should be followed.

7. OTHER CONSIDERATIONS

- None
- See over